

HD SDI DVR TSR-Series



Full HD In Live & Playback

HD over coaxial cable – No IP network required

Features

- 4, 8, 16ch HD SDI DVR with H.264 compression
- HD SDI video input and recording in full HD
- HDMI & VGA Output Full HD
- HD video over coaxial cable : No latency & no extra installation cost for HD video
- Programmable spot out : 1 VGA & 1 BNC spot out supported
- External storage with E-SATA
- Mirroring, Auto-backup

Description

Newly presented "HD SDI DVR" is a powerful DVR displaying & recording in Full HD. It enhances security capability by providing real time live and playback in HD.

It doesn't require no IP experience and complicated installation as it can be installed under existing coaxial cabling without network configuration. Powerful network extensibility is provided by supporting various web connection with IE, Safari, Firefox & etc. and smart phone application with iPhone & Android.

Specification

MODEL		TSR-4000	TSR-8000	TSR-1600	
Compression Algorithm		Video : H.264, Audio : G726			
Operating System		Embedded Linux			
Multi-Operation		Pentaplex (Live, Recording, Playback, Backup, Network)			
Video Input	HD SDI	4CH	8CH	16CH	
Video Out	HDMI	1			
	VGA / Composite	1 / 1 (Test Mode)			
Audio	Input	4	8	8	
	Output	1 (HDMI, RCA)			
Interface	Internal HDD	4 x SATA HDD (Up to 3TB)			
	USB 2.0, RS-485	2 x USB, 1 x RS-485			
	E-SATA	1			
	Ethernet	1			
	Sensor Input	4	8	8	
	Alarm Output	4 (2xRelay, 2xTTL)			
Live	Display Mode	1, 4	1,4,9	1,4,9,16	
	Digital Zoom	Up to x 10			
Recording	Resolution	Max./ch	30fps	15fps	15fps
		1920x1080	60fps	60fps	120fps
		1280x720	120fps	120fps	240fps
	Mode	Manual / Continuous / Schedule / Motion / Sensor & Pre/Post			
Storage Extension		Mirroring, Auto-Backup			
Playback & Backup	Speed	Fast Forward/Backward, Step Forward/Backward			
	Search	Search by Time, Calendar , Events and First/Last Search, Preview, Thumbnail			
	Backup Device	USB Memory Stick/HDD & Backup by Network			
	Backup File Format	AVI (With or Without Timestamp), PS (Playback in Player)			
Events & Alarm		Email&FTP Notification / Alarm-out / Buzzer for Events & Video Loss Warning Message & Buzzer for HDD Over-Temperature Alarm & Email Notification-Schedule for Events-Triggering			
Network	Transmission	Video Dual-Stream (Local recording & Network Transmission), Mobile (Jpeg)			
		Video Resolution & Frame rates adjustable			
		Bandwidth adjustable (64/128/256/512Kbps, 1/2/4/10Mbps, Unlimited)			
	C.M.S	Live , Event Manager, E-Map, Playback, Backup , PTZ, DVR Setup			
Web	Live Monitoring, Playback, Snapshot and PTZ Control				
Smart Phone	iPhone, Android				
Operation		Front Key Buttons, USB Mouse, IR Remote Control			
Power		DC12V, 5.83A		DC12V, 6.67A	
Storage Temperature and Humidity		-20~60 °C / 20~95% RH			
Operating Temperature and Humidity		5~40 °C / 20~80% RH			
Dimension (WxDxH)		341 x 258 x 60, Packing: 374 x 383 x 126 (mm)			

*Specification is subject to change without prior notice

System configuration

