

# interVision

ADVANCES IN SECURITY SOLUTIONS



## ONVIF 5 Megapixel Dome

IP Camera



**NEW** 2012 APR. V2.0




IP Surveillance

## SPECTRA-SERIES

- 5-megapixel Sony Exmor R CMOS Sensor
- Simultaneous Multiple Streams
- Built-in SD/SDHC Card Slot for On-board Storage
- Real-time H.264, MPEG-4 and MJPEG Compression (Triple Codec) • Built-in high Sensitive Microphone • Supports ONVIF Standard to Simplify Integration and Enhance Interoperability
- Supports H/W Watchdog

# SP-Series

5 Megapixel Dome  
IP Camera



Built-in SD/SDHC Card Slot

## SPECIFICATIONS

System	CPU: HITACHI 365 SoC    Flash: 32MB    RAM: 128MB	
Image Sensor	HIGH QUALITY 5-MEGAPIXEL 1/2"SONY EXMOR R CMOS	
Lens	1/2.7" 4.2mm F1.6	
Video	H.264: 30 fps at 1280x720 , Highest Resolution: 8 fps at 2592x1920	
	MPEG4: 30 fps at 1280x720 , Highest Resolution: 8 fps at 2592x1920	
	MJPEG: 30 fps at 1280x720 , Highest Resolution: 8 fps at 2592x1920	
	Compression: H.264, MPEG-4 & MJPEG Streaming:	
	Triple Codec (H.264, MPEG-4, JPEG) Selectable	
	Support Simultaneous multiple streams	
Image Settings	Adjustable image size, quality, and bit rate	
	Time/Date stamp and text caption overlay.	
	Configurable brightness, contrast, saturation, sharpness, white balance and exposure AGC, AWB, AES, BLC	
	BNC connector for video output ; NTSC/PAL video output switch	
Audio	Format	MPEG-4 AAC audio encoding G.711 audio encoding
	Built-in high sensitive microphone with 5M maximum audible area.	
	Supports audio mute	
Networking	Interface	10/100 Mbps Ethernet, RJ-45
	Supported Protocol	IPv4, TCP/IP, DHCP, HTTP, FTP, SMTP, RTSP, SNTP, DNS
	Supported Browser	Microsoft Internet Explorer 6.0 or above
Alarm And Event Management	Motion Detection	
	Event notification using SMTP or FTP	
Users	16 clients on-line monitoring at the same time	
	Multi-level user access control with password protection	
On-board Storage	SD/SDHC card slot : Stores snapshots and video clips	
Maintenance	Supports online firmware upgrade	
I/O	RJ-45 Ethernet x 1, Power connection x 1, SD-card slot x 1	
Power	DC12V, AC24V, PoE (OPTIONAL)	
Weight	About 305 g	
Dimensions	W: Φ120mm    H: 92mm	
Operating Environments	Temperature: 0 ~ 45 °C	
	Humidity: 90%	

★Version updating is not going to inform, please check the on-going updating information

■ DISTRIBUTED BY

