



High Bandwidth SOHO KVM Kit

Packaged Included All Necessary Cables

Introduction

Controlling multiple PCs from One Keyboard, Mouse and VGA Monitor. KVM switch is loaded with features such as hot-key, front panel push button and auto scan control. It has complete keyboard and mouse emulation for simultaneous PCs boot-up process

Features

- No Power Adapter And Software Required
- High Video Resolution Support Up To 2048 x 1536
- Support Up To 400MHz Bandwidth
- Auto Scan Mode Support With All Models
- Save Your Money, Time, Space, Equipment & Power..
- compact size design, easy portable
- Support Microsoft Intellimouse, Microsoft Optical Mouse, Microsoft Intellimouse explorer, Logitech Net Mouse...etc..
- Support DOS, Win3.X, Win95/98/98SE/ME/XP/2000/NT, Netware, Unix, Linux
- Hot Plug - Add or Remove Connected PCs for Maintenance Without Powering Down the KVM switch or PCs.
- No Software Required, PC selection via Push Buttons, Hot Keys
- Power Free – No power adapter needed
- Auto Scan Mode for monitoring PCs
- Keyboard status restored when switching PCs
- LED Display for easy status monitoring
- Buzzer sound for switching port confirmation
- Provides 2 / 4 Ports series with PS2, USB and PS2 / Audio Models

Taiwan / Head quarters
Edimax Technology Co., LTD.
TEL: 886-2-2299-5648
FAX: 886-2-2299-5647
sales@edimax.com.tw

China
Beijing EdimaxScience &
Technology Co., LTD.
TEL: 8610-6213-9288
FAX: 8610-6213-9231
sales@edimax.com.cn

U.S.A.
Edimax Computer Company
TEL: 1-408-496-1105
FAX: 1-408-980-1530
sales@edimax.com

Latin America
TEL: 1-786-845-8099
FAX: 1-786-331-8490
sales_latinamerica@edimax.com

Europe
Edimax Technology Europe B.V.
TEL: 31-499-377344
FAX: 31-499-372647
sales@edimax.nl

U.K.
Edimax Technology (UK) Ltd.
TEL: 44-870-7740226
FAX: 44-870-7740227
info@edimax.co.uk



2 / 4 Ports KVM Switch Kit

Model	PS2 KVM		PS2 KVM With Audio		USB KVM	
	EK-2PSK	EK-4PSK	EK-2PAK	EK-4PAK	EK-2USK	EK-4USK
Max PC Connections	2	4	2	4	2	4
PC Port & Display LED	2	4	2	4	2 x USB-B 2 x VGA	4 x USB-B 2 x VGA
Console Port	1				2 x USB-A 2 x PS2	4 x USB-A 2 x PS2
PC Port Connector (All Female)	PS/2 Keyboard mini-Din 6 pin PS/2 Mouse Mini-Din 6 pin VGA HDDB 15pin				USB Type B receptacle VGA HDDB 15pin Female	
Console Port Connector (All Female)	PS/2 Keyboard mini-Din 6 pin PS/2 Mouse Mini-Din 6 pin VGA HDDB 15pin				USB Type A Receptacle PS2 Keyboard mini-Din 6 pin PS2 Mouse mini-Din 6 pin VGA HDDB 15 pin	
PC Selection	Hot Key / Button					
3 in 1 Cable	2 x 1.8M	4 x 1.8M	2 x 1.8M	4 x 1.8M	2 x 1.8M	4 x 1.8M
Audio Cable	N/A		2 x 1.8M	4 x 1.8M	N/A	
Scan Intervals	8 Sec				5,10,20,30,40,50,60,70,80,90, 100 sec.	
Resolution	2048 x 1536					
Bandwidth	400MHz					
Housing	Plastic					
Operation Temperature	0~50 Degree C					
Humidity	0~90%, Non-Condensing					
Weight (g)	627g	1183g	787g	1503g	684g	1313g
Dimension	116X85X32	185X91X29	116X85X32	185X91X29	118X87X34	186X92X33