THE TRISTAR® SERIES

9 Single Colors



TRISTAR®-E27

 ϵ

FLECTRONIC SPECIFICATIONS

PARAMETERS	TRISTAR-E27
ELECTRICAL:	
Power Supply Voltage (Typ.) Power Supply Current Power Consumption	100 VAC ~ 240 VAC <100mA <5W
OPTICAL:	
Operating Life Beam Angle (without lens) Beam Angle (with lens)	>35,000 hrs. 60° 30°
ENVIRONMENT:	
Operation Temperature Storage Temperature Operation Humidity	-20~50°C -40~60°C 10~90%

9 Different Single Color LED Lamps Available:



Taiwan Operations: Color Stars, Inc.

Grass Green

10F, No. 566 Jung Jeng Rd. Sindian City Taipei County 231, Taiwan, R.O.C.

Tel: +886-2-8667-6600 Fax: +886-2-8667-1400 Email: sales@colorstars.com Website: www.colorstars.com

TRISTAR®-E27 5W LED Lamps


TriStar® E27 5 watt LED lamps are available in 9 single colors.

TRISTAR®-E27


Features

- High power 5W LED
- High luminous intensity output
- Min. 70% lumen maintenance after 35,000 hours
- Higher energy efficiency than incandescent and halogen lamps
- Cool beam (no UV or thermal radiation)
- Safety compliance: CE; RoHS compliant; EU-LVD conformity

DIMENSIONS DIAGRAMS



TRISTAR-E27-L has a lens. It has a beam angle of 30°.



TRISTAR-E27-CRY has a crystal face.

ColorStars Group

Headquarters: ColorStars Group

300 Center Ave., Suite 202 Bay City, MI 48708 USA Tel: 989-509-5924 Fax: 989-509-5924

Email: sales@colorstars.com Website: www.colorstars.com