




ENFIS UNO Plus Array Ultra-Violet (UVA) 375nm Technical Specification


Electro-Optical Characteristics

Item	Min	Typ	Max
Rated Current I_f (mA)		1.4	
Forward Voltage V_f (Volts)		36	
Peak Wavelength λ_p (nm)	370	375	380
Spectral Width $\Delta\lambda$ (nm)	6	10	20
Total Radiant Flux F_R (mW)		850	
Radiant Flux Density ϕ_{Rf}/dA (mW/cm ²)		739	
Total Luminous Flux Φ_v (Lumen)		-	
Luminous Flux Density Φ_v/A (Lumen/cm ²)		-	
Total Electrical Power P (W)		50	




All measurements performed at heatsink temperature 25°C


Spectral Data



Angular Distribution



LIV Graph



Heat Generation

Proper thermal design of the end product is of paramount importance. The operational junction temperature of each LED chip should be kept below 125°C.

Please contact Enfis for further support in this matter.

Handling LED Array

Contact with the encapsulant on the surface of the LED array must be avoided to prevent damage.

Do not apply pressure to the encapsulant or allow it to come into contact with the sharp objects.

During operation the encapsulant will be hot and contact should be avoided.

Static Electricity

Care must be taken when handling, these products are sensitive to static electricity. Observe static handling precautions



Cleaning

Avoid touching the LED array surface.

To clean – BLOW surface with either dry air or nitrogen gas

Eye Safety Precautions

The light output of the products may cause injuries to human eyes in circumstances where the products are viewed directly with unshielded eyes for more than a few seconds.



Please refer to IEC 60825-1:2001 for further information.

ENFIS LIMITED
TECHNIM 2, KING'S ROAD
SWANSEA WATERFRONT
SWANSEA SA1 8PJ UK

TEL +44 (0)1792 485960
FAX +44 (0)1792 485337
WWW.ENFIS.COM

ENFIS E

UNO Plus Array UV Rev. 2 May 08



ENFIS UNO PLUS Array Ultra-Violet (UVA) 375nm

Smart, powerful, compact, efficient, reliable light

Features & Benefits

- Intense, high-power UV spot source
- Tuned for pumping phosphors
- Ultra-high power density
- Long-life and reliable, high-performance due to excellent thermal conductivity
- Simple integration via connectorized PCB with mounting holes

Outline Specification

- 850mW typical power
- 1cm² Aperture
- 739mW/cm² power density
- Input power: 50W
- Typical thermal resistance <1°C/W

Light Engine Integration

Enfis can eliminate the time, cost and risk of integration by offering our arrays as part of a complete light engine solution

Thermal Management

Enfis arrays are designed to provide excellent thermal conductivity and to be integrated effectively with thermal hardware to ensure optimum performance and life.

Optics


Enfis UNO arrays provide a compact spot source with Lambertian emission characteristics. Enfis technical experts can advise a range of optical solutions to match your requirements.

Power Management

Enfis provides a range of feature-rich, powerful drivers and power supplies for our arrays. Our applications team can provide you with a solution for your specific requirements.

Applications & Markets

- Photo curing
- Non-Destructive Testing
- Sterilisation
- Lighting



ENFIS LIMITED
TECHNUM 2, KING'S ROAD
SWANSEA WATERFRONT
SWANSEA SA1 8PJ UK

TEL +44 (0)1792 485960
FAX +44 (0)1792 485537
WWW.ENFIS.COM

ENFIS 

UNO PLUS Array UV Rev.2 May 08