



ENFIS QUATTRO Array Blue 465nm

Smart, powerful, compact, efficient, reliable light

Features & Benefits

- Intense, high-power Blue spot source
- Ultra-high power density
- Long-life and reliable, high-performance due to excellent thermal conductivity

Outline Specification

- 66000mW typical power:
- 16cm² Aperture
- 4125mW/cm² power density
- Input power: 384W

Light Engine Integration

Enfis can eliminate the time, cost and risk of integration by offering our arrays as part of a complete light engine solution

Smart Array Technology

Light output from Enfis Arrays can be monitored and controlled via a patent-pending integrated photo-detection system, enabling precise control of light output.

Thermal Management

Enfis arrays are designed to provide excellent thermal conductivity and to be integrated effectively with thermal hardware to ensure optimum performance and life.

Optics


Enfis UNO arrays provide a compact spot source with Lambertian emission characteristics. Enfis technical experts can advise a range of optical solutions to match your requirements.

Power Management

Enfis provides a range of feature-rich, powerful drivers and power supplies for our arrays. Our applications team can provide you with a solution for your specific requirements.

Applications & Markets

- Neo-natal
- Dental: filler curing and whitening
- Non-Destructive testing
- Forensic investigation
- Backlighting
- Effect lighting
- Epoxy/Adhesive Curing



ENFIS LIMITED
TECHNIUM 2, KING'S ROAD
SWANSEA WATERFRONT
SWANSEA SA1 8PJ UK

TEL +44 (0)1792 485660
FAX +44 (0)1792 485537

ENFIS 




Enfis QUATTRO Blue 465nm


Technical Specification

Electro-Optical Characteristics


Item	Min	Typ	Max
Rated Current I_f (mA)		12000	
Forward Voltage V_f (Volts)		32	35
Peak Wavelength λ_p (nm)	455	465	475
Dominant Wavelength λ_d (nm)	461	471	481
Spectral Width $\Delta\lambda$ (nm)	20	25	35
Total Radiant Flux Φ_R (mW)	50000	66000	
Radiant Flux Density $d\Phi_R/dA$ (mW/cm ²)	3125	4125	
Total Luminous Flux Φ_L (Lumen)		3300	
Luminous Flux Density Φ_L/A (Lumen/cm ²)		206	
Total Electrical Power P (W)		384	420




Spectral Data



Angular Distribution



LIV Graph



Heat Generation

Proper thermal design of the end product is of paramount importance. The operational junction temperature of each LED chip should be kept below 125°C. Please contact Enfis for further support in this matter.

Handling LED Array

Contact with the encapsulant on the surface of the LED array must be avoided to prevent damage. Do not apply pressure to the encapsulant or allow it to come into contact with the sharp objects. During operation the encapsulant will be hot and contact should be avoided.

Static Electricity

Care must be taken when handling, these products are sensitive to static electricity. Observe static handling precautions



Cleaning

Avoid touching the LED array surface. To clean – BLOW surface with either dry air or nitrogen gas

Eye Safety Precautions

The light output of the products may cause injuries to human eyes in circumstances where the products are viewed directly with unshielded eyes for more than a few seconds.



Please refer to IEC 60825-1:2001 for further information.

ENFIS LIMITED
TECHNIUM 2, KING'S ROAD
SWANSEA WATERFRONT
SWANSEA SA1 8PJ UK

TEL +44 (0)1792 485660
FAX +44 (0)1792 485537

ENFIS

Quattro Array 465nm Rev. 1, Sep 07