


TALEXconverter 0010 K700 10VA 700 mA
Constant current converter


- constant current converter 700 mA for TALEXeos modules
- constant output current 700 mA DC; ±5 %
- universal supply voltage range
- SELV
- over-temperature protection
- overload protection by limitation of output power


- compact housing for luminaire installation
- connection cable with wire end ferrules length: approx. 500 mm
- identification of polarity secondary: + red / - black
- white metal housing – potted
- protection rating IP 67

Packaging:
box of 20

Designed according to:
EN 55015
EN 61000-3-2
EN 61000-3-3
EN 61347-1
EN 61347-2-13
EN 61547
EN 62384

type		TALEXconverter 0010 K700 10VA 700 mA
article number		24139072
primary voltage	V _{AC}	120/230/240
primary voltage range	V _{AC}	100-264
primary voltage range	V _{DC}	120-240
input current at 230V 50Hz	A	0.12-0.25
frequency	Hz	0/50/60
efficiency at load > 5W	%	> 75
output current	A _{DC}	0.700
secondary voltage	V _{DC}	15.2
output power	W	10.6
ambient temperature ta	°C	-25 → +50
max. case temperature tc	°C	90
weight	g	90
dimensions LxWxH	mm	87 x 35 x 28
fixing centres (D)	mm	93

Wiring diagram TALEXconverter 0010 K700 with TALEXeos modules



Number of TALEXeos modules connected to TALEXconverter 0010 K700

colour	P211-2	P214	P215	P216
red, amber	5	n.A.	n.A.	n.A.
green, blue, white	4	1	—	—



TALEXeos modules must be wired in series connection to the constant current converter TALEXconverter 0010 K700.