


**TALEXconverter 0030 K700 30VA 700 mA**  
**Constant current converter**


- constant current converter 700 mA for TALEXeos modules
- constant output current 700 mA DC; ±5 %
- universal supply voltage range
- SELV
- over-temperature protection
- overload protection by limitation of output power


- connection cable with wire end ferrules length: approx. 500 mm
- identification of polarity secondary: + red / - black
- white metal housing – potted
- protection rating IP 67

**Packaging:**  
box of 20

**Designed according to:**  
EN 55015  
EN 61000-3-2  
EN 61000-3-3  
EN 61347-1  
EN 61347-2-13  
EN 61547  
EN 62384

TALEXconverter 0030 K700 30VA 700 mA	
type	
article number	24139073
primary voltage	V <sub>AC</sub>
primary voltage range	120/230/240
primary voltage range	V <sub>AC</sub>
primary voltage range	100-264
input current at 230V 50Hz	V <sub>DC</sub>
input current at 230V 50Hz	120-240
frequency	A
frequency	0.2-0.5
efficiency at load > 5W	Hz
efficiency at load > 5W	0/50/60
output current	%
output current	> 75
secondary voltage	A <sub>DC</sub>
secondary voltage	0.700
output power	V <sub>DC</sub>
output power	8-48
ambient temperature ta	W
ambient temperature ta	30
max. case temperature tc	°C
max. case temperature tc	-25 → +50
weight	°C
weight	90
dimensions LxWxH	g
dimensions LxWxH	300
fixing centres (D)	mm
fixing centres (D)	133 x 40 x 31
fixing centres (D)	142

## Wiring diagram TALEXconverter 0030 K700 with TALEXeos modules



## Number of TALEXeos modules connected to TALEXconverter 0030 K700

colour	P211-2	P214	P215	P216
red, amber	3-16	n.A.	n.A.	n.A.
green, blue, white	4-12	1-3	1	1

**!** TALEXeos modules must be wired in series connection to the constant current converter TALEXconverter 0030 K700.