


SPECIFICATIONS FOR UPEC LAMP TYPE RED LED

MODEL: UE-LR500NR0-1XE

Features

- High Luminous intensity
- Standard T-1 diameter package
- General purpose leads
- Reliable and rugged

Package Dimensions



Part NO.	Chip Material	Lens Color	Source Color
UE-LR500NR0-1XE	AlGaInP	Water Clear	Red

Notes

1. All dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25\text{mm}$ (.010") unless otherwise noted.
3. Protruded resin under flange is 1.5mm (.06") max.
4. Lead spacing is measured where the leads emerge from the package.

			Approved	Checked	Symbol	UPEC LED	
			Joseph	Stone	Name	UE-LR500NR0-1XE	
B	JAN/19/05	Mark			Date	Description Approve	WIENDS051

Absolute Maximum Ratings at Ta=25

Parameter	Symbol	Max	Unit
Power Dissipation	PD	100	mW
Pulse Forward Current	IPF	100	mA
Forward Current	IF	30	mA
Reverse Voltage	VR	5	V
Operating Temperature Range	Topr	- 40 to + 80	°C
Storage Temperature Range	Tstg	- 40 to + 80	°C
Lead Soldering Temperature [1.6mm (0.063inch) From Body] 260 °C For 5 Seconds			

Electrical / Optical Characteristics at Ta=25

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	Iv	1500	3300	---	mcd	IF=20mA
Viewing Angle	2θ _{1/2}	---	30	---	Deg	IF=20mA
Dominant Wavelength	λ _d	620	625	635	nm	IF=20mA
Forward Voltage	V _F	1.5	---	2.4	V	IF=20mA
Reverse Current	I _R	---	---	100	μA	VR = 5V

BIN	LQ	LR	LS	LT	---	---
Range	1500-2200	2200-3300	3300-4900	4900---	---	---

Measurement Uncertainty of the Luminous Intensity: ± 15%

Measurement Uncertainty of the Dominant Wavelength: ±1nm

Measurement Uncertainty of the Forward Voltage: ±0.1V


Notes

- Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
- θ_{1/2} is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- The dominant wavelength (λ_d) is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.


			Approved	Checked	Symbol	UPEC LED
			Joseph	Stone	Name	UE-LR500NR0-1XE
					Drawing No	WIENDS051
B	JAN/19/05					
Mark	Date	Description Approve				

Typical Electrical / Optical Characteristics Curves


Spectrum Distribution




Forward Current VS. Forward Voltage




Luminous Intensity VS. Forward Current



Forward Current VS. Ambient Temperature



Radiation Diagram



			Approved	Checked	Symbol	UPEC LED
			Joseph	Stone	Name	UE-LR500NR0-1XE
B	JAN/19/05				Drawing No	WIENDS051
Mark	Date	Description Approve				

Reliability Test Items and Conditions

No.	Item	Test Conditions	Test Hours / Cycle	Sample Q'ty	Ac/Re
1	Solder Heat	TEMP : 260 ±5	5 sec	22 pcs	0/1
2	Temperature Cycle	H : +85 30min. ∩ 5min. L : -35 30min.	50 cycle	22 pcs	0/1
3	Thermal Shock	H : +85 ∩ 5min. L : -35 5min.	50 cycle	22 pcs	0/1
4	High Temperature Storage	TEMP : 85	1000 hrs	22 pcs	0/1
5	Low Temperature Storage	TEMP : -35	1000 hrs	22 pcs	0/1
6	DC Operating Life	I _F = 20mA	1000 hrs	22 pcs	0/1
7	High Temperature / High Humidity	65 / 85 ~ 90% R.H.	1000 hrs	22 pcs	0/1

Judgment Criteria

Forward Voltage Vf	V _{fmax} Increase < 1.2x
Reverse Current Ir	I _{rmax} Increase < 2x
Luminous Intensity Iv	Iv Decay < 50%

Note : Measurement shall be taken after the tested samples have been returned to normal ambient conditions (generally after two hours)

			Approved	Checked	Symbol	UPEC LED
			Joseph	Stone	Name	UE-LR500NR0-1XE
B	JAN/19/05				Drawing No	WIENDS051
Mark	Date	Description Approve				