




**XILVER™**  
Dynamic LED Fixtures

**RainDrop™**

RainDrop™ is a flexible high power LED system using Lumileds Luxeon LEDs. A RainDrop™ system is available with single color RainDrop™ light sources or with color changing light sources. Each light source is individually controllable with a DMX-512 controller. The complete RainDrop™ system is IP65 rated and thus suitable for outdoor applications.

**RainDrop™ RGB System**



**Creates 16 Million Colors**

Produces virtually any color with RGB color (Red, Green and Blue) mixing with 3 Luxeon high power LEDs (1 x 1 Watt Red, 1 x 1 Watt Royal Blue, 1 x 2 Watt Green). We use 2 Watt green for brighter whites, yellows, greens and pastel colors. A RainDrop™ has a standard beam angle of 120°. Optional lenses for narrower beams are available.


**Control**

A RainDrop™ RGB System can be controlled by any DMX-512 controller. One RainDrop™ RGB system operates on 12 DMX channels; Red intensity, Green intensity and a Royal Blue intensity channel for each of the four RainDrops in an RGB system.

**Power**

The RainDrop™ RGB System operates on 100-230 VAC/50-60Hz HZ and has a total power consumption of 20 Watt.

**RainDrop™ Mono System**



**Colored or White LED Light**

In a RainDrop™ Mono System each RainDrop™ has Luxeon High Power LEDs with the same color. A RainDrop™ Mono system is available with 1, 2, 3 or 4 Watt light sources in different colors. A RainDrop™ has a standard beam angle of 120°. Optional lenses for narrower beams are available.

**Control**

A RainDrop™ Mono System can be controlled by any DMX-512 controller. One RainDrop™ Mono system operates on 12 DMX channels. One intensity channel for each RainDrop™ in a RainDrop™ Mono system. Xilver™ Serial Interface for firmware updates and future control features via DMX bus.

**Power**

The RainDrop™ RGB System operates on 100-230 VAC/50-60Hz HZ and has a total power consumption of 20 Watt.

**RainDrop™ RGB and Mono Size & Weight**

RainDrop™: Dia. x h.: ø 70 mm x 37 mm (ø 2.76 in. x 1.46 in.).  
Weight: 0,2 kg (0.44 pound).  
Controller: l x w x h: 200 mm x 120 mm x 90 mm (7.87 in. x 4.72 in. x 3.54 in.).  
Weight: 1 kg (0.44 pound).  
RainDrops and Controller are IP65 rated and thus suitable for outdoor use.

**RainDrop™ System Items:**

RainDrop™ RGB System	106005	RainDrop™ Red System 2 Watt	106015	RainDrop™ Royal Blue System 3 Watt	106025
RainDrop™ White System 1 Watt	106006	RainDrop™ Green System 2 Watt	106016	RainDrop™ Amber System 3 Watt	106026
RainDrop™ Warm White System 1 Watt	106007	RainDrop™ Blue System 2 Watt	106017	RainDrop™ White System 4 Watt	106027
RainDrop™ Red System 1 Watt	106008	RainDrop™ Royal Blue System 2 Watt	106018	RainDrop™ Warm White System 4 Watt	106028
RainDrop™ Green System 1 Watt	106009	RainDrop™ Amber System 2 Watt	106019	RainDrop™ Red System 4 Watt	106029
RainDrop™ Blue System 1 Watt	106010	RainDrop™ White System 3 Watt	106020	RainDrop™ Green System 4 Watt	106030
RainDrop™ Royal Blue System 1 Watt	106011	RainDrop™ Warm White System 3 Watt	106021	RainDrop™ Blue System 4 Watt	106031
RainDrop™ Amber System 1 Watt	106012	RainDrop™ Red System 3 Watt	106022	RainDrop™ Royal Blue System 4 Watt	106032
RainDrop™ White System 2 Watt	106013	RainDrop™ Green System 3 Watt	106023	RainDrop™ Amber System 4 Watt	106033
RainDrop™ Warm White System 2 Watt	106014	RainDrop™ Blue System 3 Watt	106024	RainDrop™ UFO Cover	106034



**XILVER™**

Stationsstraat 44a 6247 BL Gronsveld (The Netherlands)  
Phone: +31 43 408 51 00 Fax: +31 43 408 50 99  
email: info@xilver.nl

[WWW.XILVER.NL](http://WWW.XILVER.NL)

©2004 Xilver, b.v. All Rights Reserved. All Specifications are subject to change without notice.  
Xilver™, Logo, Droplet™ and Sparkle™ Are Registered Trademarks of Xilver™ b.v.

