

MY69

VERSATILE DMMAT LOW COST

- 3 3/4 digits LCD,max. reading 3999
- Auto/manual ranging
- Data hold, auto-power off
- Relative measurement
- Full ranges protection
- High safety design

Technical specifications

DCV: 400m/4/40/400/1000V, $\pm 0.5\%$

ACV: 400m/4/40/400/750V, $\pm 0.8\%$

DCA: 400 /4m/40m/200m/10A, $\pm 1.0\%$

ACA: 400 /4m/40m/200m/10A, $\pm 1.2\%$

OHM: 400/4k/40k/400k/4M/40M , $\pm 0.8\%$

CAP: 4000p/40n/400n/4 /40 /200 F, $\pm 5.0\%$

FREQ: 10/100/1k/10k/100k/1M/30MHz, $\pm 1.5\%$

Duty cycle: 0.1%~99.9%, $\pm 2.5\%$

Audible continuity: <50

Diode test: 1.5V/0.6mA

Transistor h_{FE} : 0~1000

Dimensions: 91x189x31.5mm, ~250g

Battery: 1.5Vx2, AA size

Accessories: holster

Note: same function as XB2003, MY99



REF: 010069X10E0

✓CE (EMC), UL, CE (LVD)

Sinometer