



REF: 019600X1350

✓ CE (EMC), □ UL, □ CE (LVD)

VC9808+

PROFESSIONAL DMM + LCR

- 3 1/2 digits LCD, max. reading 1999
- Measures frequency to 10MHz, capacitance to 200 μ F, inductance to 20H & temperature!
- Peak hold, LCD backlight
- **Enhanced protection** on all ranges: over-voltage discharge capacitors, PTC, metal board shielding, etc.
- Improved auto-power off circuit
- Safety as per IEC1010-1 Cat.II 1000V

Technical specifications

DCV: 200m/2/20/200/1000V, $\pm 0.5\%$

ACV: 200m/2/20/200/700V, $\pm 1.0\%$ (40~400Hz)

DCA: 2m/20m/200m/20A, $\pm 0.8\%$

ACA: 2m/20m/200m/20A, $\pm 1.2\%$

OHM: 200/2k/20k/200k/2M/20M/2000M Ω , $\pm 0.8\%$

CAP: 20n/200n/2 μ /20 μ /200 μ F, $\pm 2.5\%$

IND: 2m/20m/200m/2/20H, $\pm 2.5\%$

TEMP: -40 to 1000 $^{\circ}$ C, $\pm 0.8\%$

FREQ: 2k/20k/200k/2M/10MHz, $\pm 0.5\%$

Audible continuity, transistor h_{FE} & diode test

Battery: 9Vx1, 6F22

Dimensions & weight: 190x88.5x27.5mm, ~320g

Accessories: holster, temp. probe